T5 LED TUBE

JEELIGHTING

JEE-T5®



FEATURES AND SPECIFICATIONS

Construction

- 4FT T5 LED Tube
- Milky cover
- Installation: Bypass Ballast(Direct Wire)
- Lamp Holder: Medium Bi-Pin (G5)
- Housing: Aluminum+PC

Electrical

- Input Voltage: 120-277Vac 50/60Hz
- Wattage: 24W
- Color: 4000K or 5000K
- 150 Lumens per Watt
- Wiring connection: double end

Applications

- Offices, retail, schools, restaurants, healthcare, residential, and hospitality applications.

Installation

- Replacement for conventional fluorescent lamp
- Operating temperature: -20°C ~ 45°C
- Damp or Dry Location only

Listing

- ETL Listed

Warranty

- 5-year limited warranty

Specs at a Glance	* Nominal Wattage (Switchable)
Model	ORM-T51224B-XX
Wattage (W)*	24W
Lumens (lm)	3600lm
CCT (K)	4000K/5000K for option
Efficacy (LPW)	150LM/W
CRI	≥ 80
Input Voltage	120-277VAC, 50/60Hz
Operating Temp	-20°C ~ 45°C
Certifications	ETL
Warranty	5-year limited warranty

T5 LED TUBE

JEELIGHTING

Ordering Information

Model	Description
ORM-T51224B-XX	T5 LED Tube 4FT 24W 4000OK or 5000K Milky Cover ,150lm/w

Dimensions




LAMP DIMENSIONS	
A	1163mm
B	1149mm

Dimensions

1) Turn off the power to the light fixture before installation
2) Open the diffuser from the light fixture
3) Remove the fluorescent tubes and ballast
4) Connect L and N line as shown on the right
5) Plug LED tube into lamp holders and close the diffuser
6) Turn on the power and check the light distribution angle

WIRING METHOD



Packing Information

Model number	L /inch	W/inch	H/inch	QTY/ctn	G.W./pc	CTN QTY/pallet
ORM-T51224B-XX	46.8	6.3	6.5	25	18.5	1250pcs